

559.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® BayTrail-M N2930 SOC
- Onboard INTEL® BayTrail-M N2930 1.83GHz Quad Cores CPU
- Onboard SAMSUNG 2G/1333MHz DDR3L Memory
- Onboard 1\* 32G M-Sata SSD
- Support DirectX 11 3D Graphics Acceleration
- Support 1\* PCI-E Gigabit LAN
- Support HDMI Output
- Equipped with 802.11 b/g/n WIFI card & External Antenna
- Support 1\*Mini PCI-E Socket(Half size)
- Support 1\* USB2.0 Port
- Support 1\* USB3.0 Port
- 36mm thin, slice design
- IP65 Rating(Option)
- VESA mount(75mm x 75mm)

| Panel               |                             |
|---------------------|-----------------------------|
| Panel Spec          | HPC-070A                    |
| Viewable Size Image | 7.0 inch With LED Backlight |
| Active Area         | 153.6(H) x90.0(V)           |
| Resolution          | 1024 x 600 @60Hz            |
| Display Color       | 16.7M                       |

|                             |                                                                                           |
|-----------------------------|-------------------------------------------------------------------------------------------|
| Pixel Pitch                 | 0.150 x 0.150 mm                                                                          |
| Aspect Ratio                | 16:9                                                                                      |
| Contrast Ratio              | 500:1                                                                                     |
| Max Brightness              | 320 cd/m²                                                                                 |
| Viewing Angle(H/V)          | H150/V145                                                                                 |
| Response Time               | 30ms(Max)                                                                                 |
| Temperature Range           | -20°C ~ +70°C(Operating)                                                                  |
| <b>Case</b>                 |                                                                                           |
| Panel Material              | Alum                                                                                      |
| Case Material               | Iron+ Alum                                                                                |
| Color                       | Black                                                                                     |
| Coating Requirement         | Spray Paint                                                                               |
| Protection grade(IP)        | IP65(Optional)                                                                            |
| Cooling Mode                | Fanless Fully sealed design                                                               |
| <b>System Specification</b> |                                                                                           |
| Form Factor                 | 2.5"                                                                                      |
| Processor                   | INTEL® Bay Trail-M N2930 1.83GHz/QC                                                       |
| System Chipset              | INTEL® Bay Trail-M N2930 (SOC)                                                            |
| System Memory               | 2G/1333MHz DDR3L SAMSUNG DRAM                                                             |
| BIOS                        | 64MB SPI Flash ROM                                                                        |
| Ethernet                    | 1*Realtek® RTL8111G Gigabit LAN                                                           |
| Audio                       | Realtek® ALC662 HD Audio                                                                  |
| Storage                     | 1*32G M-SATA SSD                                                                          |
| WIFI Module                 | N/A(Optional)                                                                             |
| Optical Device              | N/A                                                                                       |
| Expansion                   | PCI-E mini card for WLAN                                                                  |
| Display Output              | HDMI                                                                                      |
| I/O Port                    | 1*USB3.0 1*USB2.0 1*RJ45 1*COM                                                            |
| Power Adapter               | DC-IN (12V)                                                                               |
| OS Support                  | Windows 7/8.1/10                                                                          |
| Temperature                 | Operating -10 ~ +70°C                                                                     |
| Humidity                    | 20%~90% (non condensing)                                                                  |
| Shock                       | Operating 15G 11ms duration                                                               |
| Vibration                   | Operating 5~500Hz/1 Grms                                                                  |
| Net Weight (kg)             |                                                                                           |
| Dimension                   | 192.0*129.0*36.0mm                                                                        |
| Certification               | FCC CE ROHS                                                                               |
| Other                       | Support Non wire I.O interface output                                                     |
| <b>Other Information</b>    |                                                                                           |
| Application                 | Commercial Banking Digital Signage<br>Industrial Automation                               |
| Special Features            | Metal design, compact slice                                                               |
| Other                       | Optional wall hanging telescopic bracket, etc., can also be used as the embedded security |